

1046-BULK SKIP



The 1046 bulk skip has been designed to meet the everyday requirements of moving anything from waste and rubbish through to materials and concrete around site.

Supplied with lifting eyes to the top to ensure an even lift and extra eyes to the rear to aid in tipping of the unit.

Product Code	SWL (kg)	Capacity (ltrs)	Length (mm)	Width (mm)	Weight (kg)
1046-8	1000	500	500	550	140
1046-10	1500	750	1000	600	160
1046-12	2000	1000	1000	650	180
1046-14	3000	1500	1000	750	270
1046-16	4000	2000	1200	750	320
1046-18	6000	4000	1500	750	400

NOTES

The following instructions must be read and understood by each intended user of this equipment; if there is anything you do not understand contact Eichinger Equipment Ltd.

Ensure the equipment is adequate for the job you need to carry out.

You must not operate this equipment if you are under the influence of alcohol, drugs or if you are feeling unwell.

A risk assessment should be carried out prior to moving or using this equipment.

The following PPE (Personal protective equipment) should be worn when using this equipment:

Gloves / Goggles / Hard Hat / Steel Toecap boots / Hi-Vis Vest

We also suggest suitable clothing should be worn.

Familiarise yourself with the equipment, its use and how it works!

As this equipment is used at multi-level, ensure the intended area for use is clear of overhead cables and power lines or similar hazards which may affect its safe use. This equipment must always be used in conjunction with your site safety policies.

The work area must be clear of obstructions with adequate space for the operative to work safely around the equipment. Check and ensure the equipment is inspected and in a safe condition prior to its use. Also ensure that its load is stable and secure.

SETUP & OPERATION

The 1046 Bulk Skip is designed for use with a 4 leg chain. Each pair of lifting eyes are labelled below.

Lifting eyes A&B are used for transportation of the skip, B&C are used for emptying the skip. The skip must never be transported using lifting eyes B&C.

Ensure the skip is landed on a flat and even surface prior to filling. When filling ensure that the load does not exceed the stated swl, is evenly spread throughout the skip and is kept below the height of the sides of the skip.

To transport the skip attach a suitably rated 4 leg chain to lifting eyes A&B on both sides of the skip ensuring the hooks are securely closed prior to lifting. Once happy that the hooks are secure, raise the skip just off of the ground and check the skip is balanced. You may now transport the skip to it's required destination ensuring you adhere to you lift plan / method statement.

To discharge the skip it must first be landed on an even and level surface. Remove the chain hooks from lifting points A and attach them to lifting points C. Ensure all operatives are away from the working area. The skip will be discharged by lifting slowly, tag lines can be attached to manouvre the skip into the required position. Once the skip has been emptied, land the skip gently and remove the lifting hooks from point C and re-attach to points A. The skip can now be transported away from the discharge zone.

