

1061-MANHOLE RING CLAMPS



Torsionally rigid, light-weight hollow steel construction for the transportation and placement of manhole rings. The pipe tackle complies with official labour safety regulations and is equipped with a safety lock. Inadvertent slipping of the load through the claws is prevented by a spring on each clamp.

Advantages:

Clamping range adjustable by a special screw
Heavy-duty galvanized chains in accordance with DIN 5688.5

Appearance may vary from picture above.

Stock Items.

Product Code	SWL (kg)	CLAWS	Face Mat	Clamp Range (mm)	Depth	Chain Length (m)	Pipe Size	Weight (kg)
1061.2	1500	3	Ribbed	0-130	200	2.30	3m Max	34
1061.5	3000	3	Ribbed	10-180	220	2.50	3m Max	58

Stock Items from EU HQ -Ask for lead time.

Product Code	SWL (kg)	CLAWS	Face Mat	Clamp Range (mm)	Depth	Chain Length (m)	Pipe Size	Weight (kg)
1061.1	1500	3	Ribbed	0-130	200	1.70	2m Max	31
1061.2	1500	3	Ribbed	0-130	200	2.30	3m Max	34
1061.3	1500	3	Rubber	0-75	200	1.70	2m Max	32
1061.4	3000	3	Ribbed	10-180	220	1.80	2m Max	54
1061.5	3000	3	Ribbed	10-180	220	2.50	3m Max	58
1061.6	3000	3	Rubber	10-135	220	1.80	2m Max	56
1061.7	4000	4	Ribbed	50-180	220	2.50	3m Max	83

NOTES